

HORIZONTAL BALER EQUIPMENT





HORIZONTAL BALER EQUIPMENT

EF 600 S-AUTO

A semi-automatic horizontal baler designed for compact, high-density waste processing. It handles plastic film, PET bottles, cardboard, and mixed packaging waste with precision and reliability.

The closed-gate design ensures tighter bales, while its robust build and low-maintenance components make it ideal for continuous operation.



- · Heavy-duty closed gate for tighter, stackable bales.
- Hydraulic locked gate for smooth and safe operation.
- Double-cutting blades improve efficiency and extend cutter life.
- Trunnion-mounted cylinder reduces torque and seal wear.
- High-quality hydraulic valves from Taiwan ensure stable performance.



Compact footprint suits limited space without compromising output.



Operator safety with two-hand controls and hydraulic door lock.



Low maintenance with durable components and simplified servicing.

SPECIFICATIONS

Machine Weight

Baler Dimensions (WxHxD)	6100x2000x1400 mm
Chamber Size (LxWxH)	2400x980x780 mm
Bale Size	1000x1000x800 mm
Throughput	1-2 tons/hour
Power Supply	415V, 3-phase with D curve breaker
Motor	18.5 kW
Hydraulic Pressure	60 Tonnes
Oil Capacity	550L
Cycle Time (unload)	23 Seconds

5.2 Tonnes